

*Hot cleaners for workshop and production*

**ph-cleantec**  
*clean and safe performance*

*Time-consuming hand cleaning  
was yesterday. The future belongs  
to the low pressure cleaners.*



**Industry**



**Food/pharmaceutical/  
biotec**



**Catering**



**Building service**



*The clever alternative to hand cleaning or high pressure cleaners:  
**Low pressure hot cleaner 1000 SRK***

**If high pressure is out of question and hand cleaning takes too much time ...**

## Low pressure hot cleaner series 1000 SRK

Well-established methods such as high pressure cleaners are unsuitable for a variety of cleaning and maintenance tasks. Particularly in sensitive surroundings or at difficult to access points even cleaning professionals frequently have no alternative except the conventional brush and rags.

With the series 1000 SRK ph-cleantec now offers the clever alternative to hand cleaning and high pressure: The new production model is a compact version of the proven low pressure hot cleaners which have successfully been used in the industry for years. The patented ph-cleantec technology operates with a water temperature of 95° C and an adjustable pressure of 3-8 bar and is suitable for various cleaning and maintenance tasks. Thanks to the low weight of only approx. 50 kg the new unit can easily be transported and used even in the smallest of areas.

**Particularly contract cleaning companies where the benefits of using the new 1000SRK will ensure that they use the best available technology to maintain a competitive advantage.**

### Small but powerful

Handy, efficient and versatile – indoors and outdoors:

- Machines/installations
- Solar systems
- Exhaust systems
- Filtration systems
- Outdoor installations (awnings)
- Fire remedial action
- Radiators and much more

	1000 SRK-EA	1000 SRK-AS
	With direct connection to the mains water	With pump to scavenge water from a separate tank
Working pressure	approx. 3 – 7.5 bar	approx. 3 – 7.5 bar
Spray/Water consumption	1.0 – 1.8 l/min	1.0 – 1.8 l/min
Operating temperature	95 °C in 60 sec	95 °C in 60 sec
Current type	3P-N-PE/400V/50Hz,16A	3P-N-PE/400V/50Hz,16A
Rated input heating system	10 KW	10 KW
Connecting cable	8 m	8 m
Spray hose lance	5 m	5 m
Pistol with quick-disconnect coupling	Standard with 600 mm lance	Standard with 600 mm lance
Dimensions (LxWxH)	92 x 45 x 48 cm	92 x 45 x 48 cm
Water supply	External connection	scavenging from sep. tank
Weight empty	approx. 48 kg	approx. 55 kg
Filtering	n.a.	30 µm
Noise level	<70dBA	<70dBA

n.a. = non applicable

Technical modifications reserved

With model 1000 SRK-AS-EA both versions are combined; switching between scavenging and mains water is made by a three-way valve.

### Cleaning of tool machines

With the 1000 SRK models from ph-cleantec it is possible to clean with coolant as well as with cutting oil. With model 1000 SRK-AS the cleaning fluid is scavenged directly from the machine tool coolant tank and automatically filtered.

**Recommended by leading suppliers of coolants and lubricants**



Your distributor:

ph-cleantec GmbH  
Gutenbergstraße 14 | 70736 Fellbach  
Germany

Telefon: +49 711 518 06-00

Telefax: +49 711 518 09-94

Email: info@ph-cleantec.com

[www.ph-cleantec.com](http://www.ph-cleantec.com)