

# LUBRIVAC 200

## Swarf and oil vacuum with discharge system

- Powerful industrial vacuum for liquids and swarf
- Flux inversion system for liquid discharge (100L/min)
- Integrated sieve grid basket for solid / liquid separation
- Optional PPL filter for oil/coolant filtration
- Float device automatically prevents overfilling when tank is full
- Tangential suction inlet with integrated cyclone
- 3 powerful single-phase motors



<b>Power supply</b>	V - Hz	230 - 50
<b>Power</b>	kW	3
<b>Insulation class</b>		F
<b>Max water lift</b>	mmH <sub>2</sub> O	2500
<b>Max air flow</b>	m <sup>3</sup> /h	540
<b>Suction inlet / Ø</b>	mm	50
<b>Liquids capacity</b>	lt.	200
<b>Solids capacity</b>	lt.	40
<b>Noise level (EN ISO 3744)</b>	dB (A)	73
<b>Dimensions</b>	cm	63x115x147h
<b>Weight</b>	kg	165
<b>Oil mist filter</b>		3D Superweb
<b>Diameter</b>	mm	475
<b>Media, class (IEC 60335-2-69)</b>		PPL + M
<b>Discharge system</b>		<b>Flux inversion</b>
<b>Discharge speed</b>	lt / min	100
<b>Floating device</b>		Yes
<b>OPTIONAL EXTRAS</b>		
PPL300 - PPL filter 300 micron	+	Filter basket
PPL100 - PPL filter 100 micron	+	Filter basket
CART90 - Cart filter kit 90 micron	+	Outlet filtration
CART10 - Cart filter kit 10 micron	+	Outlet filtration
PUMP - 300 lt/min discharge pump	+	Simultaneous pump