

# LUBRIVAC 400

**Swarf and oil vacuum with discharge system**

- Powerful 3 phase industrial vacuum for liquids and swarf
- Integrated hopper with sieve grid to separate and dispose swarf chips
- Flux inversion system for liquid discharge (100L/min)
- Optional PPL filter for oil/coolant filtration
- Float device automatically prevents overfilling when tank is full



<b>Power supply</b>	V - Hz	400 - 50
<b>Power</b>	kW	4
<b>Electric protection</b>	IP	55
<b>Insulation class</b>		I
<b>Max water lift</b>	mmH <sub>2</sub> O	3600
<b>Continuous water lift</b>	mmH <sub>2</sub> O	3000
<b>Max air flow</b>	m <sup>3</sup> /h	400
<b>Suction inlet I Ø</b>	mm	50
<b>Liquids capacity</b>	lt.	400
<b>Solids capacity</b>	lt.	50
<b>Noise level (EN ISO 3744)</b>	dB (A)	76
<b>Dimensions</b>	cm	659x154x170h
<b>Weight</b>	kg	270
<b>Oil mist filter</b>		3D Superweb
<b>Diameter</b>	mm	475
<b>Media, class (IEC 60335-2-69)</b>		PPL + M
<b>Filter (optional)</b>		Cartridge Oil Water Repellent
<b>Surface, diameter</b>	cm <sup>2</sup> -mm	27.000 - 325
<b>Media, class (EN 1822-5)</b>		H13
<b>Discharge system</b>		<b>Flux inversion</b>
<b>Discharge speed</b>	lt / min	150
<b>Floating device</b>		Yes

## OPTIONAL EXTRAS

PPL300 - PPL filter 300 micron	+	Filter basket
PPL100 - PPL filter 100 micron	+	Filter basket
CART90 - Cart filter kit 90 micron	+	Outlet filtration
CART10 - Cart filter kit 10 micron	+	Outlet filtration
PUMP - 300 lt/min discharge pump	+	Simultaneous pump