

LUBRIVAC 80

Swarf and oil vacuum with outlet pump and filtration

- *Powerful industrial vacuum for liquids recovery and filtration*
- *Stainless steel construction*
- *Optional pump and filter for quick discharge of the liquids*
- *Integrated sieve grid basket for solid / liquid separation*
- *Tangential suction inlet with integrated cyclone*
- *2 powerful single-phase motors*
- *Float device automatically prevents overfilling when tank is full*
- *Capability to vacuum and pump out liquids simultaneously with the*
- *powerful submerged pump (100 lt/min)*
- *Cartridge filter kit available allowing filtration to 10 micron*



Technical data		LUBRIVAC 80
Power supply	V - Hz	230 - 50
Power	kW	2
Insulation class		I
Max waterlift	mmH ₂ O	2500
Max air flow	m ³ /h	360
Suction inlet / Ø	mm	80
Capacity	lt.	80
Discharge system		<i>Immersion pump(100lt/min)</i>
Noise level (EN ISO 3744)	dB (A)	76
Dimensions	cm	53x66x107h
Dry primary filter¹		
Surface, diameter	cm ² -mm	8.000 - 420
Media, class / Media, (IEC 60335-2-69) ²		Nylon + Polyester - L
Wet primary filter		
Surface, diameter	cm ² -mm	8.000 - 420
Media, class (IEC 60335-2-69) ²		<i>Polypropylene - 300µ</i>